


Ball valves EKO

Chrome plated angle valve





| Code | Dimensions | | | | | | | | EAN13 |
|---------|------------|----|----|----|----|------|------|----|---------------|
| | Size | Α | L | | Lk | d | d1 | h | LANIS |
| 1482110 | 1/2"-3/8" | 55 | 81 | 12 | 44 | G3/8 | G1/2 | 25 | 5907451906224 |
| 1482120 | 1/2"-1/2" | 55 | 81 | 12 | 44 | G1/2 | G1/2 | 25 | 5907451906231 |
| 1482130 | 1/2"-3/4" | 55 | 81 | 12 | 44 | G3/4 | G1/2 | 28 | 5907451906248 |

Product usage:

In cold and hot water systems and central heating installations as shut off valves

Type:

Angle valves

Guarantee:

25-year

Technical data/Operating parameters:

Max pressure: 1,0 MPa, Max temperature: 90°C

Used materials:

body, ball with stem: brass;

rosette: stainless steal;

seal housing: polyacetal (POM);

ball with stem and housing seal: rubber seal NBR;

handle: ABS

Finish:


body, handle: chrome



Ball valves EKO

Chrome plated angle valve





| Code | Dimensions | | | | | | | | EAN13 |
|---------|------------|----|----|----|----|------|------|----|---------------|
| | Size | A | L | | Lk | d | d1 | h | LANIS |
| 1482110 | 1/2"-3/8" | 55 | 81 | 12 | 44 | G3/8 | G1/2 | 25 | 5907451906224 |
| 1482120 | 1/2"-1/2" | 55 | 81 | 12 | 44 | G1/2 | G1/2 | 25 | 5907451906231 |
| 1482130 | 1/2"-3/4" | 55 | 81 | 12 | 44 | G3/4 | G1/2 | 28 | 5907451906248 |

Product usage:

In cold and hot water systems and central heating installations as shut off valves

Type:

Angle valves

Guarantee:

25-year

Technical data/Operating parameters:

Max pressure: 1,0 MPa, Max temperature: 90°C

Used materials:

body, ball with stem: brass;

rosette: stainless steal;

seal housing: polyacetal (POM);

ball with stem and housing seal: rubber seal NBR;

handle: ABS

Finish:


body, handle: chrome



Ball valves EKO

Chrome plated angle valve





| Code | Dimensions | | | | | | | | EAN13 |
|---------|------------|----|----|----|----|------|------|----|---------------|
| | Size | Α | L | | Lk | d | d1 | h | LANIS |
| 1482110 | 1/2"-3/8" | 55 | 81 | 12 | 44 | G3/8 | G1/2 | 25 | 5907451906224 |
| 1482120 | 1/2"-1/2" | 55 | 81 | 12 | 44 | G1/2 | G1/2 | 25 | 5907451906231 |
| 1482130 | 1/2"-3/4" | 55 | 81 | 12 | 44 | G3/4 | G1/2 | 28 | 5907451906248 |

Product usage:

In cold and hot water systems and central heating installations as shut off valves

Type:

Angle valves

Guarantee:

25-year

Technical data/Operating parameters:

Max pressure: 1,0 MPa, Max temperature: 90°C

Used materials:

body, ball with stem: brass; rosette: stainless steal;

seal housing: polyacetal (POM);

ball with stem and housing seal: rubber seal NBR;

handle: ABS

Finish:

body, handle: chrome