


## **Anti-contamination valves PURE**

## Shot blasted anti-contamination valve





| DN | Code    | Dimensions |        |    |     |      |    |    | EAN13         |
|----|---------|------------|--------|----|-----|------|----|----|---------------|
|    |         | Size       | D      |    | L   | Н    | S  | S1 | LANIS         |
| 15 | 1901000 | 1/2"       | G1/2   | 11 | 65  | 21,5 | 26 | 16 | 5907451940860 |
| 20 | 1901050 | 3/4"       | G3/4   | 13 | 75  | 24   | 31 | 16 | 5907451940877 |
| 25 | 1901100 | 1"         | G1     | 14 | 90  | 27   | 38 | 16 | 5907451940884 |
| 32 | 1901150 | 1 1/4"     | G1 1/4 | 16 | 100 | 30   | 48 | 16 | 5907451940891 |

## **Product usage:**

For use in water supply systems as protection against backflow.

Type:

Anti-contamination valves

**Guarantee:** 

25-year

**Technical data/Operating parameters:** 

Max pressure: 1,0 MPa, Max temperature: 65°C

**Used materials:** 

body, plug: brass;

check valve: made by Neoperl; check valve spring: stainless steel;

plug seal and check valve seal: rubber NBR

Finish:

body, plug: brass